



LANIER

**MP 2352/MP 2852/
MP 3352**

Advanced capabilities in a secure, eco-friendly design

This innovative digital imaging system offers an exciting combination of multifunction versatility, affordability and convenience to customize document management workflow and enhance office productivity



Perform more tasks more efficiently

Expectations are high. You're facing more tasks, more challenges—and less time. So why not demand more from your multifunction system? The LANIER® MP 2352/MP 2852/MP 3352 offers unmatched versatility and innovative security for superior productivity and efficiency. It provides copy, print, scan and fax capabilities in a compact design so you can produce a wide range of jobs with exceptional quality. Plus, it incorporates a host of sustainable, eco-friendly features that can enable fast-paced offices to save money while conserving energy. Use it as your workhorse device to streamline workflow from creation to finishing, or integrate it into a comprehensive Managed Document Services (MDS) strategy and improve productivity while reducing total cost of ownership.

Enhance Productivity

Accomplish every task with incredible speed and convenience. The Lanier MP 2352/MP 2852/MP 3352 offers all-in-one performance for fast, cost-effective workflow.

- Deliver exceptional multifunction performance with built-in printing, copying, color scanning and faxing. The MP 2852/MP 3352 is available in two configurations—a standard scan/print version and a highly-configurable copier version, which can also be modified to print, scan or fax to suit your office environment. The MP 2352 is available in a standard scan/print configuration.
- Generate up to 33 black-and-white pages-per-minute and proceed to the next job quickly.
- Execute workflows seamlessly with a wide range of document distribution tools and widgets that can be tailored for your office for maximum convenience.
- Reprint, refax or scan instantly with the built-in Document Server. It stores up to 3,000 frequently-used documents to expedite workflow.



The Lanier MP 2352/MP 2852/MP 3352 offers versatile multifunction performance, innovative security and advanced distribution capabilities in a compact, environmentally-friendly design.

MP 2352/MP 2852/MP 3352



Load scanned documents to portable media using Scan-to-Media capabilities with the USB/SD card slot and print TIFF, PDF and JPG files virtually anywhere.

Share More Efficiently

With its wide range of scanning capabilities, this digital imaging system enables quick electronic document capture and convenient distribution options for incredible flexibility, productivity and value.

- Capture documents in monochrome or in vibrant color and reduce file sizes with high-compression PDF for faster transmission and printing without compromising image quality.
- Distribute documents instantly with Scan-to-Email or automate document sharing and archiving with Scan-to-Folder.
- Employ Scan-to-URL for network flexibility. Users can store the document on the Hard Disk Drive to reduce network traffic and view and download files via Web browser.
- Preview electronic documents as full-color thumbnails for accurate review that can enhance efficiency while minimizing wasted supplies.

Deliver High-Quality Results

The Lanier MP 2352/MP 2852/MP 3352 offers powerful network printing to ensure fast-moving workflows and affordable output.

- Simplify print jobs with the icon-driven, preset PCL6 user interface driver and optional genuine Adobe® PostScript3® drivers.
- Enjoy seamless integration with Windows, Macintosh, Unix and AS/400 environments and a host of standard or optional interfaces to ensure that local network requirements are met.
- Modify queues for print jobs at any time with the Job Function List feature and meet even the most ambitious deadlines.
- Expedite jobs with PDF Direct Print. Users can print PDFs without opening Adobe Acrobat or taxing the network.
- Avoid print bottlenecks with Auto Job Promote. This feature holds a job when a resource is not available—such as a different paper size—and automatically prints the next job in the queue.



Color scanning combined with innovative Scan-To capabilities promotes cost-free document distribution and less taxing network traffic.

Outstanding Efficiency in a Compact Design

50-Sheet Automatic Reversing Document Feeder (standard)

Scan multi-page and mixed size originals quickly and easily.
(Optional for the MP 2852/MP 3352 copier only configurations)

500-Sheet External Finisher (optional)

Realize greater cost savings and productivity by printing reports and presentations in-house.

1,000 Sheet Booklet Finisher



1,000 Sheet Finisher

500-Sheet Internal Finisher

Finish In-House with Style

Produce compelling, professionally finished documents and minimize outsourcing. Choose from a variety of optional finishers to design a complete end-to-end document production solution that meets your unique application demands.

1 x 500 and 1 x 550-Sheet Paper Trays (standard)

Front-facing, user-adjustable trays accommodate a wide range of paper stocks and sizes, including envelopes.

1 x 550 Sheet Paper Tray* (optional)

Provides lower height making it easy for all users to access.

2 x 550-Sheet Paper Tray* (optional)

Add more paper capacity for larger jobs and uninterrupted printing and copying.

2,000-Sheet Large Capacity Tray* (optional)

Increase total system volume up to 3,150 sheets and add versatility for less reloading. (Letter-size sheets only for LCT)

Cabinet Stand* (optional)

Add a convenient storage space for supplies when the standard paper supply meets your needs.

*Cannot be combined with other optional paper sources.



MP 2352/MP 2852/MP 3352



Intuitive 8.5" Color Control Panel

This easy-to-use control panel simplifies operations.

One-Bin Tray (optional)

Separate copy output from fax/print output.

Duplex Unit (standard)

Support environmental initiatives, cut paper use in half and save on supply costs by printing double-sided documents.

100-Sheet Bypass Tray (standard)

Print envelopes, labels, transparencies and more on a variety of paper types and sizes.

***Choose the Configuration
that Best Meets Your
Office Requirements***



Configuration	Copier	Copy / Print / Scan
Speeds Available	28 ppm, 33 ppm	23 ppm, 28 ppm, 33 ppm
ARDF	Optional	Standard
Print/Scan Connectivity	Optional	Standard
Fax	Optional	Optional
Security	Standard DataOverWriteSecurity & HDD Encryption	Standard DataOverWriteSecurity & HDD Encryption
System Memory (Std./Max.)	512 MB / 1 GB	1 GB/1 GB
Hard Disk Drive	Optional	Standard 120 GB
Personal Paperless Document Manager	Optional	Standard 1 License

Cost-Efficient Document Management

Management Made Easy

Engineered for maximum convenience, the Lanier MP 2352/MP 2852/MP 3352 simplifies administrative tasks—including system management, device monitoring and troubleshooting.

- Access a wide range of system settings including supply levels and job details, assign e-mail notification to key team members, cancel jobs and reboot the system remotely with Web Image Monitor.
- Use Web SmartDeviceMonitor to configure, monitor and manage your entire fleet of connected Lanier devices—right from your desktop.
- Promote proactive maintenance with automated alerts for low supplies and errors with Auto-Email Notification.
- Monitor systems with @Remote. The built-in web-enabled support application automates meter submissions, critical event notifications and remote firmware updates.

Advanced Document Security

Help ensure document integrity at every stage of the creation and distribution process with comprehensive security that protects your most important information assets.

- Protect sensitive documents on the hard drive with the standard DataOverwriteSecurity System (DOSS). It automatically overwrites the hard drive to prevent retrieval of confidential information when enabled.
- Add a powerful layer of security with standard HDD Encryption and encode stored documents for maximum protection from hackers.
- Safeguard critical data during transmission with Encrypted PDF Transmission. Use it to scramble and encrypt transparent and vulnerable data, including user name and password.
- Ensure accurate user authentication with a variety of methods, including user codes, LDAP, Windows Authentication and card based authentication solutions.

Fast Fax Transmission

Handle any workload—whether it's one page or hundreds—with innovative faxing features that simplify management and expedite delivery.

- Send and receive faxes electronically with Internet faxing, using either a PC or conventional fax numbers via IP to save on transmission costs and paper.
- Preview pages prior to transmission to decrease errors and detect blank pages.
- Route inbound faxes to an e-mail address or network folder to ensure timely, accurate delivery and distribution.

Set output limits for individuals and groups with the Quota Setting feature to effectively control print costs.

Store up to 3,000 frequently-used documents in the Document Server for instant reprinting, refaxing and scanning.

Minimize access to sensitive documents. Locked Print allows users to delay printing until they enter a password at the device.

MP 2352/MP 2852/MP 3352

Enable Mobile Workers

Give mobile users an easy way to print documents while on the go without compromising security.

- Print documents, e-mails and Web content from anywhere with optional HotSpot Printing. Users can forward documents to the MFP via PDAs or other Internet-enabled devices without installing drivers or software.
- Accommodate visitors, such as employees visiting branch offices, with the Mail-to-Print feature. This allows users to send emails with attachments directly to the MFP to print PDF/JPG files automatically without installing print drivers.

Customize Workflows

The Lanier MP 2352/MP 2852/MP 3352 offers innovative tools that accommodate the unique demands of your environment and streamline business-critical activities.

- Customize MFP touch-screen menus directly from the PC quickly without IT support and create secure, searchable PDFs from text files, spreadsheets and scanned documents with Personal Paperless Document Manager (PPDM) software.
- Expedite data entry at the MFP and navigate embedded software programs—including GlobalScan NX, eCopy ShareScan, NSi AutoStore and other applications—with the optional USB keyboard.*
- Connect to Cloud applications such as DocumentMall. Documents can be securely scanned to a folder in DocumentMall or downloaded for printing.
- Develop customized applications using Embedded Software Architecture, a Java-compatible Software Development Kit (SDK).

Sustainable Efficiency

Conserve energy while boosting productivity. Lanier has incorporated a variety of environmentally-friendly features that conserve time and money.

- Reduce paper consumption by printing double-sided documents—and reducing output by up to half—with standard automatic duplexing.
- Start printing and copying quickly. The Lanier MP 2352/MP 2852/MP 3352 warms up in as few as 4.5 seconds and recovers from Sleep Mode as quickly as 4 seconds.
- Save energy with fast first-copy times. This digital imaging system can produce a first copy in as little as 14 seconds.

*Native embedded scanning is not supported.



Fax documents right from your desktop to maximize convenience and boost efficiency.



Print from mobile devices to HotSpot-enabled MFPs and printers for fast, convenient printing on the go.

The Total Green Office Solution



Lanier continues its long-standing commitment to developing office solutions with environmentally friendly and superior energy- and supply-saving features, without compromising productivity.

LANIER**MP 2352/MP 2852/MP 3352****ENGINE/COPIER SPECIFICATIONS**

Scanning Element	One-Dimensional Solid Scanning Through CCD
Printing Process	Single Laser Beam Scanning & Electrophotographic Printing
Toner	Dry, Dual Component
Copy Resolution	600 x 600 dpi
Quantity Indicator	Up to 999
First Copy Time	MP 2352: Less than 5.4 seconds MP 2852/MP 3352: Less than 4.5 seconds
Warm-Up Time	With Hard Disk Drive: Less than 20 seconds Without Hard Disk Drive: Less than 14 seconds
System Memory (std./max)	Copier Basic: 512 MB RAM/1 GB RAM + 120 GB HDD Print/Scan: 1 GB RAM + 120 GB HDD
Original Type	Book/Sheet/Object
Maximum Original Size	Up to 11" x 17"
Copy Size	5.5" x 8.5" to 11" x 17"
Copy Type	Plain Paper, Transparencies, Letterhead, Color Paper, Pre-Punched Paper, Envelopes, Cardstock, Recycled
Continuous Copying Speed	MP 2352: 23 copies/minute (LTR) MP 2852: 28 copies/minute (LTR) MP 3352: 33 copies/minute (LTR)
Power Source	120V/60Hz/12A
TEC Value	MP 2352: 1,870 Wh (Print/Scan) MP 2852: 2,210 Wh (Print/Scan) MP 3352: 2,511 Wh (Print/Scan)
Standard Paper Capacity	500 sheets x 1 tray, 550 sheets x 1 tray, and 100-Sheet Bypass Tray
Maximum Paper Capacity	3,150 sheets
Paper Size	5.5" x 8.5" to 11" x 17" A6 to A3, B6 to B4 14 – 28 lb. Bond/52 – 105 g/m ² (Duplex) 14 – 42 lb. Bond/52 – 157 g/m ² (Tray 1, 2 and Bypass)
Standard Output Tray Capacity	500 sheets (Letter) 250 sheets (Legal, Ledger)
Maximum Output Capacity	1,600 sheets (Bridge Unit + 1 Bin + 1,000 Sheet Finisher)
Reduction Ratios	25%, 50%, 65%, 73%, 78%, 85%, 93%, 100%
Enlargement Ratios	121%, 129%, 155%, 200%, 400%
Zoom	25% to 400% in 1% increments
Standard Features	Auto Magnification, Auto Paper Select, Auto Tray Switch, Booklet/Magazine Copy*, Center/Border Erase, Chapters, Combine Mode, Cover Insertion, Directional Magnification, Document Server (3,000 File Capacity)*, Duplex, Electronic/Rotate Sorting, Full-Color VGA Touch Screen Control Panel, Negative/Positive, OHP Slip Sheet, 8 Job Presets*, 10 Job Programs, 500 User Codes, Sample Copy, Series Copy*, User Stamps*
Dimensions (WxDxH)	
Copier Basic:	587 mm x 653 mm x 709 mm 23.1" x 25.7" x 27.9"
Print/Scan:	587 mm x 653 mm x 829 mm 23.1" x 25.7" x 32.6"
Weight	
Copier Basic:	143 lbs., 65 kg
Print/Scan:	165 lbs., 75 kg

PRINTER SPECIFICATIONS

Standard on Print/Scan Configuration / Option on Copier Basic Configuration	
Print Speed	MP 2352: 23 ppm (LTR) MP 2852: 28 ppm (LTR) MP 3352: 33 ppm (LTR)
CPU	RM7035C 533 MHz
Standard Interfaces	10Base-T/100BaseTX Ethernet, USB 2.0
Optional Interfaces	IEEE 802.11a/b/g Wireless LAN, Bluetooth, IEEE 1284 Parallel, Gigabit Ethernet
Memory Capacity	Shared with Copier
Network Protocol	TCP/IP, IPX/SPX
Network Operating Systems	Windows Vista/7/XP/Server 2003/Server 2008, Netware 6.5 or later, Unix; Sun Solaris, HP-UX, SCO OpenServer, Red Hat Linux, IBM AIX, Mac OS X 10.2 or later, SAP R/3, NDS/4 Gateway, IBM iSeries/A5/400® using OS/400 Host Print Transform, Citrix Presentation Server 4.5/Citrix Xen App 5.0

Utilities	@Remote, SmartDeviceMonitor, Web SmartDeviceMonitor, Web Image Monitor
Page Description Languages	PCL5e/6, Adobe PostScript 3, IPDS (optional)
Print Resolution	Up to 600 dpi
Fonts for PCL5e/6	45 Scalable Fonts, 6 Bitmap Fonts, 13 International Fonts
Fonts for PS3	136 PostScript Fonts
Standard Features	Sample/Locked/Hold/Stored Print

SCANNER SPECIFICATIONS

Standard on Print/Scan Configuration / Option on Copier Basic Configuration	
Scanning Speed	Embedded Scanning: 50/45 ipm (@ 200 dpi)
B&W/Color	600 dpi
Scanning Resolution	Up to 11" x 17"
Scan Area	10Base-T/100BaseTX Ethernet
Standard Interfaces	IEEE 802.11a/b/g Wireless LAN, Gigabit Ethernet
Optional Interfaces	TCP/IP, NCP, SMB, SMTP, POP 3, LDAP, FTP
Protocol	Shared with Copier
Memory Capacity	Single and Multi-Page TIFF/PDF, High Compression PDF, Single-Page JPEG
File Types	Embedded Scan-to-Email/HDD/Folder/URL and TWAIN, Color Scan
Standard Features	

FAX SPECIFICATIONS (OPTION)

Circuit	PSTN, PBX
Compatibility	ITU-T G3
Resolution	200 x 200/100 dpi 400 x 400 dpi (optional)
Compression Method	MH, MR, MMR, JBIG
Scanning Speed	0.35 seconds (LEF)
Modem Speed	33.6 Kbps with Auto Fallback
Transmission Speed	G3: 3 seconds per page (MMR Compression) G3: 2 seconds per page (JBIG Compression)
SAF Memory	4 MB standard/28 MB maximum
Max Auto Dials	320 pages/2,240 pages
Group Dials	2,000
Features	100 (max. 500 numbers per group) Dual Access, Duplex Reception, Image Rotation, 1 Hour Backup, LAN-Fax Capability*, Internet Faxing (T.37)*, IP Faxing (T.38)*, Fax Forwarding to E-Mail/HDD/Folder*
Optional Features	Simultaneous Operation of up to 3 lines (G3 x 3)

SECURITY FEATURES

Standard on Print/Scan Configuration / Option on Copier Basic Configuration	
DOSS, HDD Encryption, S/MIME, IPsec Communication, Locked Print Password Encryption, Encrypt Address Book, SSL, User Authentication, Quota Setting/Account Limit, SNMP v3, SMTP over SSL and PDF encryption	

HARDWARE ACCESSORIES

PB3120 Paper Feed Unit (Option)	
Paper Size	7.25" x 10.5" to 11" x 17"/A5 to A3
Paper Weight	14 to 42 lb. Bond/52 to 157 g/m ²
Paper Capacity	1 x 550 sheets
Dimensions (WxDxH)	22.9" x 24.8" x 4.8" 580 mm x 629 mm x 120 mm
PB3130 Paper Feed Unit (Option)	
Paper Size	7.25" x 10.5" to 11" x 17"/A5 to A3
Paper Weight	14 to 42 lb. Bond/52 to 157 g/m ²
Paper Capacity	2 x 550 sheets
Dimensions (WxDxH)	22.9" x 24.8" x 10.3" 580 mm x 629 mm x 260 mm
PB3140 Large Capacity Tray (Option)	
Paper Size	8.5" x 11"/A4
Paper Weight	14 to 42 lb. Bond/52 to 157 g/m ²
Paper Capacity	2,000 sheets x 1
Dimensions (WxDxH)	22.9" x 24.8" x 10.3" 580 mm x 629 mm x 260 mm
One-Bin Tray BN3090 (Option)	
Paper Size	5.5" x 8.5" to 11" x 17"/A5 to A3
Paper Weight	16 to 28 lb. Bond/60 to 105 g/m ²
Paper Capacity	100 sheets
500-Sheet Internal Finisher Type 3352	
Paper Size	7.25" x 10.5" to 11" x 17"/A3, A4
Paper Weight	14 lb. Bond to 140 lb. Index/52 to 256 g/m ²

Stack Capacity	500 Sheets (8.5" x 11" or smaller) 250 Sheets (8.5" x 14" or larger)
Staple Capacity	50 Sheets (8.5" x 11") 30 Sheets (8.5" x 14" or larger)
Staple Position	Top 1, Bottom 1, Left 2, Top 2
Dimensions (WxDxH)	19.5" x 18.8" x 6.4" 495 mm x 477 mm x 161 mm
Punch Kit PU3020 NA (Option)	2 or 3 hole punch
SR3070 500-Sheet Finisher (Option)	
Paper Size	7.25" x 10.5" to 11" x 17"/A3, A4
Paper Weight	14 to 42 lb. Bond/52 to 157 g/m ²
Stack Capacity	500 sheets (8.5" x 11" or smaller) 250 sheets (8.5" x 14" or larger)
Staple Capacity	50 sheets (8.5" x 11") 30 sheets (8.5" x 14" or larger)
Staple Position	Top Slant, Bottom Slant, Left 2, Top 2
Dimensions (WxDxH)	15.6" x 21.7" x 10.9" 396 mm x 551 mm x 275 mm
SR3090 1,000-Sheet Finisher (Option)	
Paper Size (Upper Tray)	5.5" x 8.5" to 11" x 17"/A6 to A3
Paper Weight (Upper Tray)	14 lb. Bond to 140 lb. Cover/52 to 260 g/m ²
Stack Capacity	Upper Tray: 250 sheets (8.5" x 11" or smaller) 50 sheets (8.5" x 14" or larger) Shift Tray: 1,000 sheets (8.5" x 11" or smaller)
Staple Capacity	500 sheets (8.5" x 14" or larger) 50 sheets (8.5" x 11") 30 sheets (8.5" x 14" or larger)
Staple Position	Top 1, Bottom 1, Left 2, Top 2
Dimensions (WxDxH)	10.7" x 20.5" x 31.2" 270 mm x 520 mm x 790 mm
SR3100 Booklet Finisher (Option)	
Paper Size (Upper Tray)	5.5" x 8.5" to 11" x 17"/A6 to A3
Paper Size (Shift Tray)	7.25" x 10.5" to 11" x 17"/A3, A4
Paper Weight	14 to 28 lb. Bond/52 to 105 g/m ² (Upper Tray); 14 lb. Bond to 140 lb. Index/52 to 256 g/m ² (Shift Tray)
Stack Capacity	Upper Tray: 100 sheets (8.5" x 11" or smaller) 50 sheets (8.5" x 14" or larger) Shift Tray: 1,000 sheets (8.5" x 11" or smaller)
Staple Capacity	500 sheets (8.5" x 14" or larger) 50 sheets (8.5" x 11") 30 sheets (8.5" x 14" or larger)
Staple Position	Top 1, Center, Left 2, Top 2
Saddle Stitch Capacity	1 set (10 sheets)
Saddle Stitch Position	Center 2 Positions
Dimensions (WxDxH)	21.1" x 23.7" x 36.7" 535 mm x 600 mm x 930 mm
Punch Kit PU3000 NA (Option)	2 or 3 hole punch
ARDF DF3060	
Standard on Print/Scan Configuration / Option on Copier Basic Configuration	
Paper Size	5.5" x 8.5" to 11" x 17", A5 to A3
Simplex Paper Weight	11 to 34 lb. Bond/40 to 128 g/m ²
Stack Capacity	50 sheets
Dimensions (WxDxH)	21.7" x 19.6" x 4.8" 550 mm x 496 mm x 120 mm

ADDITIONAL ACCESSORIES

3L68-19 USB Keyboard, ADF Handle Type C, Bluetooth Interface Unit Type D, Bridge Unit BU3050, Card Reader Bracket Type 3352, Caster Table Type D, DataOverwriteSecurity Unit Type I¹, External USB Keyboard, FAC 52 Cabinet, File Format Converter Type E, G3 Interface Unit Type 3352, Gigabit Ethernet Board Type A, Handset Type 3352, Hard Disk Drive Type 3352¹, IEEE 802.11 a/g Interface Unit Type J, IEEE 1284 Interface Board Type A, Internal Shift Tray SH3050, IPDS Unit Type 3352, Key Counter Bracket Type H, Optional Counter Interface Unit Type A, Platen Cover Type 3352¹, PostScript Unit Type 3352, Printer/Scanner Unit Type 3352¹, USB 2.0/SD Slot Type H, VM Card Type N¹, VZ G106030 Keyboard Bracket

Note: Some accessories require additional equipment or may be prerequisites for other options.

*Copier Basic Configuration requires additional accessories.

For maximum performance and yield, we recommend using genuine Lanier parts and supplies.

- 1 Copier Basic Configuration only.
- 2 ISO 15408 Certified.

www.lanier.com

Lanier, Five Dedrick Place, West Caldwell, NJ 07006

Lanier® and the Lanier Logo are registered trademarks of Ricoh Americas Corporation. All other trademarks are the property of their respective owners. The content of this document, and the appearance, features and specifications of Lanier products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Lanier makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Lanier products and services are as set forth in the express warranty statements accompanying them.

L3307

